

NEW 30-kW MODEL  
NOW AVAILABLE

QUIET, POWERFUL  
PEACE OF MIND.



48-kW Home Generator

Home and Small Business Generators

RCL Product Line – 24, 30, 38, 48 and 60 kW

**KOHLER.**  
Generators

# Home and Small Business Generators

RCL Product Line – 24, 30, 38, 48 and 60 kW

Exceptionally powerful, surprisingly quiet. Whatever the size of your home or business, there's a reliable KOHLER® generator to match. These five models feature robust 1800-rpm liquid-cooled engines and patented technology that keeps sound levels to a minimum. And now there's a 30-kW model to round out the lineup.



30RCL

### Quality – backed with a premium limited warranty.

Every KOHLER generator is meticulously quality-tested for total reliability. It comes with our premium limited 5-year, 2,000-hour protection, plus a corrosion-resistant aluminum enclosure that's built to last.

### Extremely quiet operation.

Patented technology makes operation surprisingly quiet and neighborhood-friendly, with sound levels similar to a typical central air conditioner and weekly exercises as quiet as a normal conversation.

### Protect your electronics.

Outstanding voltage and frequency regulation and ultra-low levels of harmonic distortion provide high-quality power that won't harm sensitive electronics or expensive appliances.

### Easy to install and maintain.

A simple terminal block helps streamline installation, and single-side service makes these generators easy to maintain.

### Compatible with advanced options.

Models are equipped with an RDC2 controller to manage both the generator and the transfer switch. The RDC2 is compatible with Power Relay Modules, Programmable Interface Module and OnCue® Plus Generator Management System.

Name	24 kW	30 kW	38 kW	48 kW	60 kW
Model Number	24RCL	30RCL	38RCLB	48RCL	60RCL
Rated Power LPG (Liquid Propane)/ NG (Natural Gas) (kW)	24/21	30/30	38/38	48/48	59/57
Voltage @ 60 Hz Single-Phase	120/240				
Amps LPG/NG @ 240 V Single-Phase	100/87	125/125	158/158	200/200	246/238
Engine/Alternator rpm	1800				
Three-Phase Available	Yes				
Engine	2.2 L 39 hp	2.2 L Turbo 64 hp	2.2 L Turbo 75 hp	5.0 L 89 hp	5.7 L 113 hp
	KOHLER KG2204 Naturally Aspirated	KOHLER KG2204T Turbo		General Motors Vortec	
	In-line 4			V-8	
	Hydraulic Valve Lifters				
Peak Motor Starting kVA at 240V: (35% dip for voltages below)	37	44	74	113	144
Fuel	LPG/NG				
Engine Cooling	Liquid-Cooled				
Enclosure	Corrosion-Resistant Aluminum				
Average Sound Output dBA at 23 ft (during exercise/normal operation)*	55/61	54/62	54/62	58/61	60/61
Single Point Sound Output dBA at 23 ft (during exercise/normal operation)**	53/60	54/61	54/61	56/60	58/59
Dimensions (L x W x H)	74 x 34 x 45			90 x 34 x 45	
Digital Voltage Regulation	+/- 1.0%				
Warranty	5-Year Limited				

\*8-point logarithmic average

\*\*Lowest of 8 points around the generator as compared to competitor ratings. Sound levels at other points around generator may vary depending on installation parameters.

**KOHLER**  
Generators

See the entire lineup of  
KOHLER generators from 8 to 150 kW at  
[KohlerGenerators.com](http://KohlerGenerators.com)

Form G12-430 Rev. 4/16  
© 2016 Kohler Co.  
Kohler, Wisconsin 53044  
Printed in U.S.A.  
800-4-KOHLER  
(800-456-4537)